

With adhesive liner

This is a general purpose 4:1 shrink ratio, flexible polyolefin tubing with a thermoplastic adhesive inner liner. The inner liner will melt and flow to environmentally seal and protect components and interconnections.

Features & Benefits

- 4:1 shrink ratio allows for connector to cable sealing.
- Medium wall provides increased mechanical protection.
- Adhesive bonds to a wide variety of plastics, rubbers and metals including polythene, aluminium, steel and copper.
- Standard Colours: Black and transparent

Applications

- Environmentally seals and protects a wide variety of electrical applications.
- High expansion ratio for cable jacket repair without removing connectors.
- High strain relief and mechanical protection.

General Information	
Material Jacket	Polyolefin
Inner Liner	Polyamide
Shrink Ratio	4:1
Operating Temperature	-55°C to +110°C
Dielectric Strength	12KV/mm
Installation Temperature	80°C to +110°C
Specifications	UL E853381 RoHS AMS DTL 23053/4

Technical Data			
Part Number	Minimum supplied ID (mm)	Maximum Recovered ID (mm)	Recovered Wall thickness (mm)
104-4/1	4.0	1.0	1.00
104-8/2	8.0	2.0	1.00
104-12/3	12.0	3.0	1.40
104-16/4	16.0	4.0	1.78
104/-24/6	24.0	6.0	2.25
104-32/8	32.0	8.0	2.54
104-52/13	52.0	13.0	2.54

Need more technical advice? Require samples for evaluation?

Our customer service team can help and can be contacted either by phone or email on +44 (0) 1285 762000 or sales@adtech.co.uk.