

## Polyolefin Heat Shrink-Size Specification for Standard Wall

Size	As supplied (mm)		After Recovery (mm)	
	I.D.	Average Wall Thickness	Max. I.D.	Average Wall Thickness
<b>Φ1.2 (3/64")</b>	1.1 +/- 0.2	0.15 +/- 0.05	0.6	0.22 +/- 0.10
<b>Φ1.6 (1/16")</b>	1.5 +/- 0.2	0.15 +/- 0.05	0.8	0.28 +/- 0.10
<b>Φ2.4 (3/32")</b>	2.5 +/- 0.2	0.18 +/- 0.05	1.2	0.35 +/- 0.10
<b>Φ3.2 (1/8")</b>	3.5 +/- 0.2	0.18 +/- 0.05	1.6	0.40 +/- 0.10
<b>Φ4.8 (3/16")</b>	5.0 +/- 0.2	0.25 +/- 0.05	2.4	0.50 +/- 0.10
<b>Φ6.4 (1/4")</b>	6.5 +/- 0.2	0.28 +/- 0.05	3.2	0.55 +/- 0.10
<b>Φ7.9 (5/16")</b>	8.5 +/- 0.3	0.28 +/- 0.05	4.0	0.60 +/- 0.10
<b>Φ9.5 (3/8")</b>	9.5 +/- 0.3	0.30 +/- 0.05	4.8	0.60 +/- 0.10
<b>Φ12.7 (1/2")</b>	12.5 +/- 0.3	0.40 +/- 0.12	6.4	0.65 +/- 0.10
<b>Φ16.0 (5/8")</b>	16.5 +/- 0.4	0.40 +/- 0.12	8.0	0.70 +/- 0.10
<b>Φ19.1 (3/4")</b>	19.0 +/- 0.5	0.40 +/- 0.15	9.5	0.80 +/- 0.15
<b>Φ25.4 (1")</b>	26.0 +/- 0.5	0.50 +/- 0.15	12.7	0.90 +/- 0.15
<b>Φ32.0 (1-1/4")</b>	31.5 +/- 1.0	0.50 +/- 0.15	16.0	0.95 +/- 0.15
<b>Φ38.1 (1-1/2")</b>	41.5 +/- 1.0	0.55 +/- 0.15	19.1	1.00 +/- 0.15
<b>Φ50.8 (2")</b>	51.5 +/- 1.0	0.55 +/- 0.15	25.4	1.00 +/- 0.15