



Adtex-S™ Heat Shrink Sleeving Technical Properties

| | |
|-----------------------------|--|
| Manufacturer: | Adtech Polymer Engineering Ltd |
| Product: | ADTEX-S heat shrink sleeving to suit T5, T8, T10 & T12 UVA, UVC and incandescent lamps |
| Material: | Virgin FEP polymer—fully fluorinated copolymer |
| Dimensions: | Sleeves to suit T5 lamps—minimum supplied ID 18.5mm Adtech part number: ADTEXS-14L/T5 Sleeves to suit T5 UVC lamps—ceramic ends—minimum supplied ID 21mm Adtech part number: ADTEXS-14L/T5C Sleeves to suit T8 lamps—minimum supplied ID 29.5mm Adtech part number: ADTEXS-23L/T8 Sleeves to suit T10 lamps—minimum supplied ID 36mm Adtech part number: ADTEXS-27L/T10 Sleeves to suit T12 lamps—minimum supplied ID 41mm Adtech part number: ADTEXS-32L/T12 |
| Wall thickness: | 0.25mm nominal +/-0.05mm |
| UV Data: | Transparency to UV- A, >95%, UV-C, 85% at 0.25mm thickness |
| Flame rating: | 94 V-O (UL-94) |
| Shrink temperature: | 110°C nominal |
| Working temperature: | 200°C |
| Melting point: | 260°C |
| Packaging: | Random production lengths on reels |
| Certifications: | This product is ROHS compliant IEC/BS EN 61549 compliant when used correctly. |

FDA approved raw polymers/coatings can be supplied upon request.

For more information about our FEP Lamp Coatings, please visit adtech.co.uk.

For technical assistance, contact our customer service team:

+44 (0)1285 762000 - sales@adtech.co.uk