



Anti-Static PTFE Convuluted Tubing

Our convoluted tubing can be supplied with an anti-static filler, either as a co-extrusion or a fully filled version.

During production, we continuously test tensile strength, crystallinity, diffusion and changes in length.

In addition to our standard range, we can produce custom sizes. We also offer fixed length assemblies where the ends can be supplied cuffed (straightened) and/or flanged for easy connection.



Standard Anti-Static PTFE Convuluted Tubing Sizes

DN	Inch	ID (mm)	ID Tol. (mm)	Wall (mm)	Wall Tol. (mm)	OD (mm)	OD Tol. (mm)	Pitch (mm)	BR (mm)
6	1/4"	7.70	+/-0.30	0.65	+/-0.10	11.30	+/-0.30	3.0	18
8	5/16"	8.20	+/-0.40	0.65	+/-0.10	13.00	+/-0.30	4.5	19
10	3/8"	10.10	+/-0.40	0.65	+/-0.10	16.00	+/-0.40	5.0	20
12	1/2"	14.60	+/-0.40	0.70	+/-0.15	19.50	+/-0.50	4.5	25
15	5/8"	17.10	+/-0.40	0.70	+/-0.15	23.20	+/-0.50	5.5	30
20	3/4"	21.00	+/-0.50	0.70	+/-0.15	26.50	+/-0.60	6.0	35
22	7/8"	23.50	+/-0.50	0.80	+/-0.15	29.00	+/-0.75	6.0	40
25	1"	26.40	+/-0.50	0.80	+/-0.15	29.50	+/-0.75	8.5	45
32	1 1/4"	33.00	+/-0.50	0.90	+/-0.15	34.30	+/-0.85	8.5	50

For more information about our PTFE Convuluted Tubing, please visit adtech.co.uk.

For other custom sizes or technical assistance, contact our customer service team:

+44 (0)1285 762000 - sales@adtech.co.uk